

strada

designed for
and by baristas.



Available Configurations: MP | EP | EE | AV | ABR

Available Number of Groups: 1 (EP only) | 2 | 3

Over the course of two years La Marzocco worked with thirty of the world's finest coffee professionals to design a machine. This group was known as the "Street Team"; the Strada, Italian for street, was named in their honor. A lower profile invites customer engagement in a

café setting, while also providing the barista an open, expansive work area. The Strada platform has been designed to encourage creativity and customization so that each machine can be unique. The Strada is available in 5 different configurations to meet the specific needs

of baristas and cafes around the world. All configurations are equipped with the finest La Marzocco technology and provide users great ergonomics, barista-friendly design and electronics in a machine that enables to showcase the very best of each coffee.

Dual Boilers

Separate boilers optimise espresso brewing and steam production.

Independent Saturated Boilers

Separate saturated boilers for each group head allow barista to optimise temperature for individual coffees, ensuring thermal stability.

Dual PID (coffee and steam)

Allows you to electronically control coffee and steam boiler temperature.

Insulated Boilers

Reduce energy consumption while contributing to temperature stability.

Gear Pumps - EP only

One gear pump per group delivers stable pressure control, making it possible to create and replicate pressure profiles.

Periscope Pressure Gauges - MP only

Monitor real-time pressure applied by the conical paddle valve on the coffee puck.

Adjustable Drip Tray

Allows you to use the machine with tall, to-go cups.

Proportional Steam Valve - EP, EE, AV, ABR

Lever-style activation for proportional solenoid steam valve.

Pro Touch Steam Wands

High performing steam wands that are cool to the touch.

Hot Water Economiser

Enables you to fine-tune the tap water temperature for tea.

USB - EP, AV, ABR

Making it possible to update the firmware (AV, ABR) or upload and download pressure profiles (EP).

Digital Display

Intuitive programming makes it easy to adjust machine parameters.

Integrated Scales - ABR only

Precision scales built in the drip tray provide an improved level of consistency.

Programmable Doses - EP, AV, ABR

Auto-volumetrics ensure repeatability and consistency in high-volume settings.

Eco Mode - AV, ABR

Can be programmed to enter stand-by mode, improving energy efficiency.

Internal Pump and Tank - EP 1 Group only

Self-contained 2 liter water tank and internal volumetric pump for countertop use.

Cup Warmer - 2 and 3 Groups, option

Maintain espresso and cappuccino cups evenly heated at a proper temperature.

Personalised Colours - option

Customisable colours based on the RAL colour system, on request.

Specifications	1 group (EP only)	2 groups	3 groups
Height (cm)	47.5	47.5	47.5
Width (cm)	50.5	80	100
Depth (cm)	67.5	67.5	67.5
Weight (kg)	62.5	85	102
Voltage (Single Phase)	220-240V	220-240V	220-240V
Wattege Elements	2300	5360	7325
Amps	10.5	24	31.8
Recommended CPR	15	25	32
Coffee Boiler Capacity (litres)	1.3	2 x 1.3	3 x 1.3
Steam Boiler Capacity (litres)	3.5	8.2	11.8